

TECHNICAL DOCUMENTATION

PROTECNET

ANTI DUST AGENT



APPLICATION FIELD

PROTECNET is specially designed to attract dust particles in the air. Surfaces treated with **PROTECNET** turn into a dust magnet. **PROTECNET** is effective against air pollution.

PROTECNET should be applied to dust emission points and wherever dust is a problem :

- mainly inside spray booths where air movement causes dust particles to rise from vehicle interiors as well as from the interior walls and floors of the spray booths.
- Scrap areas, grinding shops, storage areas of powder products, furnaces, hopper emptying etc...

CHARACTERISTICS

CONSUMPTION	10 M2 / Litre
PARTICULARITY	This product contains no silicone

INSTRUCTIONS FOR USE

Apply with a brush or roller on all smooth non-porous surfaces (painted steel sheets, light metal alloys, plastic materials etc...).

The addition of water is not necessary.

Approximately 15 minutes after its application **PROTECNET** begins to attract dust particles. **PROTECNET** does not lose its adhesive quality, even in temperatures of 80° C for long periods of time. Loss of adhesion indicates that **PROTECNET** is full. The first layer should be removed before applying a new one. The film can be washed.



PACKAGING

CONTAINERS	10 Litres	30 Litres
------------	-----------	-----------